

PLASCON FLOOR PAINT

PRODUCT DESCRIPTION AND USES

Plascon Floor Paint is formulated for the decoration and protection of interior concrete floors. Based on a special, tough and flexible resin and pigmented with oxide pigments, Plascon Floor Paint offers excellent adhesion to concrete floors, high opacity and good abrasion and scrub resistance.

SURFACE PREPARATION

New or old concrete floors must be clean from all contaminants. Smooth surfaces should be etched with Plascon Floor Etching Solution to form a key. Washed off with water to remove all traces of acid and allowed to dry thoroughly.

Two coats of Plascon Floor Paint is recommended for new surfaces.

FINISH

Gloss.

APPLICATION

By brush or spray.

THINNING AND MIXING

Thin with Plascon White Spirit. Stir well before use.

EQUIPMENT CLEANING

Clean the equipment immediately after use with White Spirit.

DRYING TIME

Touch dry in 4 hours. Hard dry and over-coatable in 16 hours.

COLOUR RANGE

Available in Red Oxide, Grey and Chrome Green.

SPREADING CAPACITY

10-14m² per litre on properly prepared surfaces.

PACK SIZES

1 Litre, 4 Litres, 20 Litres



Toxic/Harmful



Harmful/Irritant



Highly/Extremely
Flammable



Dangerous for the
Environment