

**PLASCON HI GLOSS ENAMEL**

**PRODUCT DESCRIPTION AND USES**

Plascon Hi Gloss Enamel is a highly durable synthetic enamel paint which is easy to apply. It is suitable for most painting jobs, on wood, plaster, metal etc. for indoors and outdoors and it produces a gloss finish. It is economical and lightfast.

**SURFACE PREPARATION**

On new wood, Plascon Pink/White Wood Primer; on steel, Plascon Zinc Chromate Free Primer. On galvanised steel, zinc, and light alloys metals, only Zinc Phosphate Primer or Wash Primer are recommended. If undercoating is desired, use Plascon Universal Undercoat. Finish off with 2 coats of Plascon Hi Gloss Enamel.

**FINISH**

Full gloss.

**APPLICATION**

Brush, roller or spray.

**THINNING AND MIXING**

Thin with Plascon White Spirit for application by brush, Synthetic Thinner for spray application.

**EQUIPMENT CLEANING**

Clean the equipment immediately after use with Plascon White Spirit.

**DRYING TIME**

Hi-Gloss dries through in 4-6 hours. Re-coatable in 16 hours.

**COLOUR RANGE**

Hi-Gloss is available in a limited number of attractive standard shades, as well as Black and White.

**SPREADING CAPACITY**

11-15m<sup>2</sup> per litre @40 microns DFT.

**PACK SIZES**

1 litre, 4 litres, 20 litres.



**Toxic/Harmful**



**Harmful/Irritant**



**Highly/Extremely  
Flammable**



**Dangerous for the  
Environment**