

**PLASCON SELF PRIMING ROOF PAINT**

**PRODUCT DESCRIPTION AND USES**

Based on a flexible alkyd and inert pigments, Plascon Roof Paint offers maximum protection for galvanized roofs and exposed Iron and Steel structures. As a flexible film coating, Plascon Roof Paint will withstand extreme weather variation and the resultant dimensional changes. It offers high opacity.

**SURFACE PREPARATION**

**New GCI Roof**

Allow the surface to etch by weathering (i.e. 6 months) or treat with Passivating Wash Solution prior to application of Roof Paint. Wash off with water to remove all traces of acid and allow to dry thoroughly. Ensure the surface is clean and dry. Apply 2 coats of Plascon Roof paint.

**Previously Painted Surfaces**

Remove all loose and flaky materials. Apply 1-2 coats of Plascon Roof Paint.

**FINISH**

Semi gloss

**APPLICATION**

Brush, roller or spray.

**THINNING AND MIXING**

White Spirit for brush application and/or Plascon Synthetic Thinner for spray application.

**EQUIPMENT CLEANING**

Clean the equipment immediately after use with White Spirit.

**DRYING TIME**

Touch dry in 15 minutes. Hard dry in 2-4 hours.

**COLOUR RANGE**

Red oxide, chrome green, white and grey.

**SPREADING CAPACITY**

9m<sup>2</sup>(100ft<sup>2</sup>) per litre @ 35 microns DFT

**PACK SIZES**

1 Litre, 4 Litres and 20 Litres.

