

PLASCON ACRYLIC PRIMER SEALER/UNDERCOAT

DESCRIPTION AND USES	Plascon Acrylic Sealer Undercoat is a copolymer based general purpose primer sealer/undercoat for untreated timber and concrete surfaces. Ideal for porous timber surfaces on which Supergloss or other decorative alkyd based enamels are to be applied. The high content of Titanium dioxide in the formulation gives excellent filling and obliterating properties. It is quick drying, water thinnable and easy to apply. It posses all the properties of a primer, sealer and undercoat. It can also be applied on concrete surfaces.
SURFACE PREPARATION	Surfaces to be painted must be clean and dry, free from oil, grease, dirt and any loose material. Apply one liberal coat to new and bare timber surfaces.
FINISH	Matt.
APPLICATION	By brush, spray or roller.
THINNING AND MIXING	Thin to brushing, spraying or rolling consistency with water. Stir well before use.
EQUIPMENT CLEANING	Clean the equipment immediately after use with clean tap water.
DRYING TIME	Completely dry and re-coatable after 4 hours.
COLOUR RANGE	White. Other pastel shades can be supplied on request.
SPREADING CAPACITY	10-13m ² Per Litre on smooth surfaces.
PACK SIZES	1 Litre,4Litres and 20 Litres.



Toxic/Harmful



Harmful/Irritant



Highly/Extremely
Flammable



Dangerous for the
Environment