

PLASCON BUDGET UNDERCOAT

PRODUCT DESCRIPTION AND USES

Plascon Budget Undercoat is an alkyd based product specially formulated to provide a flexible, non-absorbent base for Plascon Super Gloss and other gloss finishes. When applied evenly it will fill minor cracks and other blemishes. It is suitable for interior and exterior use and can be applied over an appropriate primer. It offers excellent inter-coat adhesion between primer and top-coat.

SURFACE PREPARATION

New Primed Metal, Wood or Plaster etc.

Ensure surface is clean and dry. Apply 2 coat of Budget Undercoat over the appropriate primer. Allow 16 hours drying before over-coating.

Previously painted –Unsound surfaces

Remove any loose or flaky materials. Ensure surface is clean, dry and free of other defects. Apply the appropriate patch primer to affected areas. Then slightly abrade the surface to give enhanced adhesion. Apply 2 coat Budget Undercoat.

Previously painted-Sound surfaces

Lightly abrade. Ensure the surface is clean and apply 2 coat of Budget Undercoat.

APPLICATION

Apply by brush, roller or spray.

FINISH

Matt

THINNING AND MIXING

With White Spirit. Stir well before use.

../2



Toxic/Harmful



Dangerous for the
Environment

PLASCON BUDGET UNDERCOAT

EQUIPMENT CLEANING

Clean the equipment immediately after use with Plascon White Spirit.

DRYING TIME

Overcoat after 16 hours.

COLOUR RANGE

Available in White. Other Light shades suitable for use with BS 4800 COLOUR RANGE available on request.

SPREADING CAPACITY

9-13m² at 40 microns DFT.

PACK SIZES

1 litre, 4 litres and 20 litres



Toxic/Harmful



Dangerous for the Environment