

PLASCON TRADE WALL COVER EMULSION

PRODUCT DESCRIPTION AND USES

Plascon Trade Wall Cover Emulsion is based on a copolymer emulsion and light fast pigments. It is suitable for interior and exterior applications. It has excellent hiding power and presents a matt finish. It can be used on cement, lime, plaster, as well as stone and blocks. It is economical and requires no primer on new or previously painted sound surfaces.

SURFACE PREPARATION

Surfaces to be painted must be clean and dry. No under bound or loose materials should be left prior to painting. Under bound and chalky surfaces can be treated with one coat of Plascon Binder or Plascon Penetrating Primer.

New Surfaces

Remove all nibs, efflorescence and loose materials. Dust off and fill small imperfections with crack filler. Smooth down and ensure the surface is clean and dry. Apply 3 coats of Plascon Trade Wall Cover Emulsion thinned with water to normal working consistency.

Previously Painted - Sound

Sand down to form a key for subsequent coats. Remove all loose and flaky material by scraping with a stiff fibre or nylon brush. Make good any minor imperfections with an appropriate filler. Ensure the surface is clean and dry.

Apply 3 coats of Plascon Trade Wall Cover Emulsion thinned with water to normal working consistency.

Previously Painted - Unsound

Remove all loose and flaking materials including old distemper, lime wash or cement paint, down to a firm base. Ensure the surface is clean and dry before application of 1 coat of Plascon Plasco Binder to bind and seal the surface. Apply 3 coats of Plascon Trade Wall Cover Emulsion thinned with water to normal working consistency.

.../2



Toxic/Harmful



Dangerous for the Environment

PLASCON TRADE WALL COVER EMULSION

FINISH	Matt
APPLICATION:	By brush, roller or spray gun.
THINNING AND MIXING	Thin with tap water to the required consistency.
EQUIPMENT CLEANING	Clean the equipment with water.
DRYING TIME:	Recoat after 4 hours.
COLOUR RANGE	White and Pastel shades.
SPREADING CAPACITY:	8-12 m ² perlitre @ 40 microns DFT.
PACK SIZES	4 litres and 20 litres.



Toxic/Harmful



**Dangerous for the
Environment**