

PLASCON WEATHERGUARD

PRODUCT DESCRIPTION AND USES

Plascon Weatherguard is a uniquely formulated coating based on an acrylic copolymer emulsion. Weatherguard's highly bound film offers excellent flexibility, toughness and low dust retention properties. It contains additional biocides to combat attack from mould and algae. Plascon Weatherguard gives a smooth finish and is ideal for use in coastal areas. Its unique formulation and smooth finish makes it the preferred product for hotels, high rise buildings and private housing.

SURFACE PREPARATION

New walls

Surfaces must be clean, dry and free of loose materials. Apply 3 full coats of Plascon Weatherguard, thinning down the first coat to allow maximum penetration. Allow 4 hours between coats.

Chalky/Powdery or Flaking surfaces

Using stiff fibre or nylon brushes remove all loose and friable materials. When the surface is clean, apply 1 liberal coat of Plascon Plasco Binder followed by 2 coats of Plascon Weatherguard. Allow 4 hours between coats.

Previously painted surfaces in sound condition

Sand down the existing coat to a firm base. Then apply two coats of Plascon Weatherguard. Allow 4 hours between coats.

FINISH

Low sheen.

APPLICATION

By brush, roller or airless spray

THINNING AND MIXING

Use clean tap water.

EQUIPMENT CLEANING

Clean the equipment with water.

DRYING TIME

4 hours.

.../2



Toxic/Harmful



Dangerous for the Environment

PLASCON WEATHERGUARD

COLOUR RANGE	Brilliant White and pastel shades - other shades on request.
SPREADING CAPACITY	10-12 m ² per litre at 40 microns DFT.
PACK SIZES	4 litres, 20 litres



Toxic/Harmful



Dangerous for the Environment