

## PLASCON SPECIAL WEATHERGUARD SILICONE

### PRODUCT DESCRIPTION AND USES

**Special Weatherguard Silicone** is a uniquely formulated coating based on an acrylic copolymer emulsion modified by Silicone Resin. Special Weatherguard Silicone's highly bound film offers excellent flexibility, toughness, good water bidding and dust pick up properties. It contains additional biocides to combat attack from mould and algae. Special Weatherguard Silicone gives a smooth finish and is ideal for use in coastal areas. Its unique formulation and smooth finish makes it the preferred product for hotels, high rise buildings and private housing.

### SURFACE PREPARATION

#### New walls

Surfaces must be clean, dry and free of loose materials. Apply 3 full coats of Plascon Special Weatherguard Silicone, thinning down the first coat to allow maximum penetration. Allow 4 hours between coats.

#### Chalky/Powdery or Flaking surfaces

Using stiff fibre or nylon brushes remove all loose and friable materials. When the surface is clean, apply 1 liberal coat of Plascon Plasco Binder followed by 2 coats of Plascon Special Weatherguard Silicone. Allow 4 hours between coats.

#### Previously painted surfaces in sound condition

Sand down the existing coat to a firm base. Then apply two coats of Plascon Special Weatherguard Silicone. Allow 4 hours between coats.

### FINISH

Low sheen.

### APPLICATION

By brush, roller or airless spray

### THINNING AND MIXING

Use clean tap water.

### EQUIPMENT CLEANING

Clean the equipment with water.

### DRYING TIME

4 hours.

### COLOUR RANGE

Brilliant White and pastel shades - other shades on request.

### SPREADING CAPACITY

10-12 m<sup>2</sup>per litre at 40 microns DFT.

### PACK SIZES

4 litres, 20 litres



Toxic/Very Toxic  
Harmful

Dangerous for the  
Environment