

## PLASCON ULTIMATE PTFE (WEATHERGUARD EXTREME)

|                              |  |
|------------------------------|--|
| <b>Typical uses</b>          | <p>Plascon Ultimate PTFE is a water-based coating made specially and that too uniquely formulated with special emulsions and additives to provide the ultimate protection to all buildings both old and new mainly in terms of exceptionally outstanding stain resistance.</p> <p>Plascon Ultimate PTFE is exceptionally a tough, washable, durable, stain resistant, dirt repelling matt emulsion and It is very suitable for heavily trafficked areas both interior and exterior with a 7 years warranty (Terms &amp; conditions apply as in Technical Datasheet of Weatherguard Extreme).</p> |
| <b>Pack Size</b>             | 1 Litre, 4 Litres, 20 Litres.  |
| <b>Colour Range</b>          | See appropriate Plascon colour literature. (Refer Technical Department in terms of warranty regarding colors approval for interior and exterior)   |
| <b>Film Properties</b>       | <p>Stain Resistance: Suitable.<br/>Dirt Repellant: Suitable.</p> <p>Water Resistance: Where frequent heavy condensation is likely, as in some kitchens and bathrooms, Plascon Aquashield is more suitable.</p>   |
| <b>Composition (nominal)</b> | <p>Pigment: High opacity durable Pigments.<br/>Binder: Acrylic Copolymer Emulsion.<br/>Solvent: Water.</p>   |
| <b>Application Method</b>    | Brush, roller or spray.  |
| <b>Drying Times</b>          | <p>Single coat at standard thickness:</p> <p>Touch Dry: Dependent upon temperature and humidity.<br/>Recoat: 2-4 hours.</p>  |
| <b>Practical Coverage</b>    | A guide to the practical coverage which can be achieved under normal conditions is between 10-15m <sup>2</sup> /litre.   |
| <b>Thinning</b>              | <p><b>Normal use (not to be exceeded):</b> Add up to 1½ part clean water to 4 parts paint.</p> <p><b>Conventional spray application:</b> Add up to 1½ part clean water to 4 parts paint.</p>   |



Toxic/Harmful



Dangerous for the Environment

## PLASCON ULTIMATE PTFE (WEATHERGUARD EXTREME)

### Cleaning Up

After use, remove as much paint as possible from brushes before cleaning with clean water. Do not use or store in extremes of temperature and protect from frost.

### SURFACE PREPARATION:

**New Plaster or Concrete:** For priming apply 1 coat of Plascon Acrylic Sealer Undercoat thinned with water to normal working consistency.

**Previously white washed or distempered walls:** Old coatings of white wash or distemper should be removed by wire brush or scrapping and anything remaining in the pores should be bound using 2 coats of Plascon Plasco Binder or penetrating primer and left to dry for 4 and 16 hours respectively.

Previously painted walls should be sanded down and 2 coats of Plascon Ultimate PTFE applied

Where necessary, rub down and then wipe off with a damp, lint free cloth, to avoid dust. Any surface defects should be filled with appropriate Plascon Stucco.

### SYSTEM INFORMATION:

**Stir thoroughly before use.** The normal finishing process is 2 coats of Plascon Ultimate PTFE

For more information, please contact our Technical Advisory Service on Tel: 555711.

### Hazard symbols:



Toxic/Harmful

Dangerous for the Environment