

PLASCON VINYL SILK EMULSION

PRODUCT DESCRIPTION AND USES

Plascon Vinyl Silk is a superior quality emulsion paint based on a fine particle size copolymer and lightfast pigments. With a fashionable low sheen silky appearance, exceptional toughness and is washable. It is ideal for use in high traffic areas i.e. kitchens, bathrooms, corridors, stores, passages, hospitals and food processing plants. Vinyl Silk Emulsion can be applied on plaster and stone as well as timber and should be stirred well before use.

SURFACE PREPARATION

New unpainted walls

Apply one coat of Plascon Matt Emulsion of the same colour, then two to three coats of Plascon Vinyl Silk Low Sheen Emulsion.

Previously painted walls

Remove loose, flaking and powdery paint. If necessary porous walls should be primed with two coats of Plascon Binder then apply two to three coats of Vinyl Silk Low Sheen Emulsion.

FINISH

Silky Low Sheen finish

APPLICATION

Normally by brush, roller or spray.

THINNING AND MIXING

Thin with clean tap water.

EQUIPMENT CLEANING

Clean equipment with water

DRYING TIME

Recoatable in 4 hours

COLOUR RANGE

Available in Pastel Shades selected from BS 4800 and house colours.

SPREADING CAPACITY

10 to 14 m² per litre. (This varies depending on the nature of surface.)

PACK SIZES

1 Litre, 4 Litres and 20 Litres.



Toxic/Harmful



Dangerous for the Environment